



## SWIFTZ 4T SAE 10W-40 SL, JASO MA-2

### 4T Motor-Cycle Oil

#### GENERAL PROFILE

Swiftz 4T SAE 10W-40 is a high performance four stroke motor cycle oil formulated with high quality base stocks and advanced additives. It advanced additive technology provides a strong lubricating film at high temperatures , provides a high level of engine component cleanliness and protection from wear, rust and corrosion. It is developed for use in off-road and on-road motorcycles.

#### FEATURES & BENEFITS

1. Outstanding thermal stability at elevated temperatures.
2. Excellent anti-wear protection.
3. It allows smooth gear change operations.
4. Engine protection and cleanliness.
4. Highly shear stable to enhance power and acceleration.

#### SPECIFICATION

API SL, JASO MA2

#### APPLICATION OF USE

It is recommended for all racing motor cycles where the OEM recommends this type of oil and specification. It is suitable for use in both air-cooled and liquid cooled 4T motor cycles.

PHYSICAL CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		10W-40
Density @ 25°C, g/cc	ASTM D4052	0.87
K.Viscosity @ 100°C, cSt	ASTM D445	14.20
K.Viscosity @ 40°C, cSt	ASTM D445	94.40
Viscosity Index	ASTM D2270	155
Apparent Viscosity CCS @ -25°C, cP	ASTM D5293	6400
Pour Point, °C	ASTM D97	-39
Flash Point, °C	ASTM D92	230
TBN, mg KOH/g	ASTM D664	6.6

\*Typical value does not constitute a specification

#### Health and Safety

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of the product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.