



## COOLCLEANZ COOLANT 50%

Anti-freeze/Engine Coolant

### GENERAL PROFILE

Coolcleanz Coolant 50% is pre-mixed, ready to use extended life coolant specially formulated from OAT (Organic Acids Technology) inhibitor system. It is free from nitrite, amine, phosphate or silicate (NAPS free). It provides maximum protection against deposits, rust and corrosion in engine cooling systems.

### FEATURES & BENEFITS

1. Advanced inhibitor protection for coolant systems.
2. Does not require additional supplemental coolant additives (SCAs).
3. Excellent cooling and anti-freeze protection for the cooling systems.

### SPECIFICATION

ASTM D3306, BS 6580

### APPLICATION OF USE

It is recommended to be used in majority of passenger cars, light and heavy-duty applications for on-highway, off-road, agricultural, mining and construction equipment where this is type of coolant is recommended by OEM.

PHYSICAL CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
Appearance		Green
Density @ 15°C, g/cc	ASTM D4052	1.07
Boiling Point, °C	ASTM D 1120	110
Freezing Point, °C	ASTM D 1177	-37
pH Value	ASTM D 1287	8.5
Reserve Alkalinity	ASTM D 1121	2
Corrosion Test	ASTM D 1384	Pass

\*Typical value does not constitute a specification

#### Health and Safety

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of the product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.